

Rodeon

JumboDrive

CLAUSS

The Power Pack among the TurnTables



Technical Data:

| | |
|---------------------|--|
| Type of Device | motorized TurnTable |
| Controlling Device | Notebook, Laptop, Smartphone |
| Data Interface | Bluetooth Class 1 and RS-232 |
| Storage of Data | Camera or Controlling Device |
| Camera-Triggering | Fully-automated via Camera-Trigger Cable |
| Field of View | 0 ° ... 360 ° |
| Angular Resolution | 0.0212 ° |
| Twisting Limitation | unlimited |
| Gear Steps | 17'000 Steps |
| Torque | 10'000 mNm |
| Payload | 200 kg |
| Physical Dimension | 805 mm x 721 mm x 150 mm |
| Weight | 40 kg |
| Working Temperature | 0 °C ... +45 °C |

Optional Accessories:

RS-232/USB cable set for wired control,
white 1 m Ø-acrylic glass plate

Power Supply

| | |
|-----------------|--|
| Nominal Voltage | 88 ... 132 V or 180 ... 260 V (internal switchable), 47 ... 63 Hz |
|-----------------|--|

RODEONObjectmove

Optional Softwaresuite (Windows and Mac) for Controlling the TurnTable with live Image Preview, USB Camera Control and direct Object Movie Export. Useful Controlling and Editing tools are included.

RODEON TwinTable

Exact and synchronous rotation of two plates ensure doubled Stabilization and Mounting of displayed objects.